

Magmex Fire Hose



All Synthetic, EPDM Rubberlined Fire Hoses

CONSTRUCTION

Outer jacket woven with high tenacity synthetic yarn on fully automated circular weaving looms.

INNER LINING

Ultra light weight synthetic EPDM Rubber lining having low friction loss and very high ozone resistance

CHARACTERISTICS

100% synthetic construction having:

- Resistance to sea-water and ozone
- Resistance to mildew and fungus
- High Pressure ratings
- Flexible, Compact and Easy to Clean
- Temperature range from -40°C to 100°C
- Colour : Silver White

STANDARD LENGTHS

15mtr, 18.3mtr, 22.5mtr and 30mtr

APPLICATIONS

- Fire Brigades
- Power Plants
- Railways
- Thermal Power Plants
- Pharmaceutical Industries
- And other industries
- High rise buildings
- Steel Plants
- Sailing Vessels


APPROVALS

- UL Listed under UL-19 by Underwriters Laboratory U.S.A. (Model CEP-75)
- MED WHEELMARK approved under EN 14540
- Lloyd's approved to EN 14540 Type 1
- Conforming to BS 6391 Type 1
- IRCLASS-Indian Register of Shipping (IRS approved) for use on Merchant navy Vessels
- ISI Marked

| Nominal Size (in) | Working Pressure (psig) | Proof Pressure (psig) | Burst Pressure (psig) |
|-------------------|-------------------------|-----------------------|-----------------------|
| 1 1/2" (38mm)* | 330 | 500 | 750 |
| 1 3/4" (45mm) | 330 | 500 | 750 |
| 2" (50mm) | 330 | 500 | 750 |
| 2 1/2" (63mm)* | 330 | 500 | 750 |
| 2 3/4" (70mm) | 330 | 500 | 750 |
| 3" (76mm) | 225 | 325 | 600 |
| 4" (102mm) | 150 | 250 | 450 |

*UL-19 S.P.150 psig

AN ISO 9001 - 2015 COMPANY



CHHATARIYA FIRETECH INDUSTRIES

23A SURYODAYA MILLS COMPOUND | 96 TARDEO ROAD
MUMBAI 400 034 | INDIA

PH 91 22 23513705 / 23521313 / 23510849

E-MAIL chhatariya1@gmail.com | URL www.chhatariyafiretech.in

FACTORY :

89 GIDC ESTATE, MAHUVA 364 290, GUJARAT, INDIA

PH +91 2844 228887 / 228749

E-MAIL info@chhatariyafiretech.com

URL www.chhatariyafiretech.com